



XARIS™



LED Industrial Location Lighting

XARIS light weight, high-performance LED lighting is specifically engineered for installation in environments where flammable gases, vapors, or dust are present in quantities that pose a potential risks.

Compliance

NEC/CEC Standard

CSA C22.2 No.137
CSA C22.2 No. 250.0:21
UL 1598 Wet Locations
UL 1598A Marine Outside Type (Salt Water)
UL 8750 LED Safety
FCC
IP66/67 | IK09 | 5G | NEMA 4X

Features

- Low profile design, balanced well in weight, safety and durability.
- Copper-free aluminum housing
- Corrosion resistant baked powder epoxy/polyester
- Integrated AC-In technology
- High ambient temperatures up to +80°C
- High Efficiency LED delivers up to 150 lm/W
- Universal mounting accessories for easy retrofitting
- Resistant up to 2,000 PSI of hose directed water
- Tested 1000hrs salt spray to standard ASTM"B117-11"
- Lumen Maintenance 150,000hours @L70

Warranty

5-year limited system warranty
Lumen Maintenance: L70 > 150,000 hours @ 25°C

Technical Data

Electrical

Rated Power	40 / 60 / 80 / 100 / 150 / 200W
Input Voltage	AC120V / 277V / 347V / 480V
Input Frequency	50/60Hz
Power Factor	> 0.95
Driver Efficiency	≥ 90%
Surge Protection	4kV standard

Optical

Lumen Output	6,000lm ~ 3,0000lm
Luminous Efficacy	150 lm/W
Beam Angle	110°
CCT	Amber 2700K 3000K 4000K 5000K
CRI	Ra>70

Environmental


Ambient Operating Temperature	-40°C~+80°C -40°C~+65°C (200W)
Ambient Operating Humidity	10%~90% RH
Atmospheric pressure	86~106KPa
T-Code(NEC/CEC)	Pending

Technical

Lens Material	Tempered glass
Mounting Options	Pendant / Ceiling / Wall mount / Stanchion / U-Bracket
Cable Entries	3/4" NPT
Net Weight	4.7kg (10.36 lbs)

Dimensions

unit: mm(in)



Ordering Information and Mounting Accessories

XAR	IL	OSM	TG	RV	110	5K	80	S	XXX
Model	Type	Mount Style	Lens	Voltage	Optics	Color Temp	Power	Color	Accessories
	IL	PM - Pendant mount (3/4" NPT) SBP - Swivel Bracket Pendant WM - Wall mount 90° WA - Wall mount 25° SS - Stanchion-90° (1-1/4" NPT) SSB - Stanchion-90° (1-1/2" NPT) SA - Stanchion-25° (1-1/4" NPT) SAB - Stanchion-25° (1-1/2" NPT) CJB - Ceiling junction box	TG - Clear glass FG - Frosted glass	RV - 100-277V HV - 277-480V	110 - 110°	3K - 3000K 4K - 4000K 5K - 5000K AM - Amber	40W - 6,000 lm 60W - 9,000 lm 80W - 12,000 lm 100W - 15,000 lm 150W - 22,500 lm 200W - 30,000 lm	S - Silver	SC1 PBC48 PBC60 CAB CGL PS SB1

Mounting Options



PM (Standard)
Pendant mount
3/4" NPT



SB
Swivel bracket
3/4" NPT



WM
Wall mount 90°
3/4" NPT



WA
Wall mount 25°
3/4" NPT



SS
Stanchion mount 90°
1-1/4"NPT



SA
Stanchion mount 25°
1-1/4"NPT



CJB
Ceiling junction box
3/4"NPT

SSB
Stanchion mount 90°
1-1/2"NPT

SAB
Stanchion mount 25°
1-1/2"NPT

Accessories



PBC48
Pipe clamp (M8*48mm)
for pole Ø 1-7/8"



SC1
Stainless steel
safety cable
Ø8 (4mm)



CAB
3' SEOWW-18/3 Cord
(Factory installed)
Applicable to C1D2



CGL
Cable gland
3/4" NPT
Suitable for C1D2



PBC60
Pipe clamp (M8*60mm)
for pole Ø 2-3/8"



PS
Pole stanchion
2-3/8" (60mm)



SB1
Swivel bracket
3/4" NPT

